



Product line	X-Line	K-Line	Z-Line
Insert ø 3.40 mm Distance height REF	 3.00 mm I.06.05.X300  4.50 mm I.06.05.X450	 2.00 mm I.06.05.K200  3.50 mm I.06.05.K350	
Insert ø 3.80 mm Distance height REF	 3.00 mm I.06.01.X300  4.50 mm I.06.01.X450  6.00 mm I.06.01.X600	 2.00 mm I.06.01.K200  3.50 mm I.06.01.K350	 3.50 mm I.06.01.Z350
Insert ø 4.50 mm Distance height REF	 3.00 mm I.06.02.X300  4.50 mm I.06.02.X450  6.00 mm I.06.02.X600	 2.00 mm I.06.02.K200  3.50 mm I.06.02.K350	 3.50 mm I.06.02.Z350
Insert ø 5.50 mm Distance height REF	 3.00 mm I.06.03.X300  4.50 mm I.06.03.X450  6.00 mm I.06.03.X600		 3.50 mm I.06.03.Z350  5.00 mm I.06.03.Z500
Insert ø 6.50 mm Distance height REF			 3.50 mm I.06.04.Z350  5.00 mm I.06.04.Z500
Denture magnet Distance height REF	 2.65 mm U.00.01.X265R	 5.00 mm U.00.01.K500	 3.15 mm U.00.01.Z315
Positioning cuff/ Resilience ring Resilience REF	 0.3 mm P.00.01.X1  0.3 mm P.00.01.X2	 0.00 mm P.00.01.K1  0.00 mm P.00.01.K2  0.3 mm P.00.05.K1	 0.3 mm P.00.03.Z1
Impression post Distance height REF	 6.95 mm A.00.02.X695	Please use the denture magnet for impression!	 6.95 mm A.00.02.Z695
Laboratory replica Distance height REF	 9.00 mm M.00.01.X900  9.00 mm M.00.05.X900Stainless steel	 7.50 mm M.00.01.K750	 10.00 mm M.00.01.Z1000
Torque wrench adapter	     		
We offer suitable torque wrench adapters across all product lines for numerous torque wrenches. Feel free to contact us.			

