

Systemübersicht Titanmagnetics® für Conelog

Produktlinie	X-Line		K-Line		Z-Line	
Insert ø 3,80 + ø 4,30						
Aufbauhöhe REF	3,50 mm I.58.01.X350	5,00 mm I.58.01.X500	2,50 mm I.58.01.K250	4,00 mm I.58.01.K400	4,00 mm I.58.01.Z400	
Prothesen- magnet						
Aufbauhöhe REF	2,65 mm U.00.01.X265R		5,00 mm U.00.01.K500		3,15 mm U.00.01.Z315	
Positions- manschette/ Resilienzring						
Resilienz REF	0,3 mm P.00.01.X1	0,3 mm P.00.01.X2	0,00 mm P.00.01.K1	0,00 mm P.00.01.K2	0,3 mm P.00.05.K1	0,3 mm P.00.03.Z1
Abformpfosten						
Aufbauhöhe REF	6,95 mm A.00.02.X695		Zur Abformung benutzen Sie bitte den Prothesenmagnet!		6,95 mm A.00.02.Z695	
Modellimplantat		 Edelstahl				
Aufbauhöhe REF	9,00 mm M.00.01.X900	9,00 mm M.00.05.X900	7,50 mm M.00.01.K750		10,00 mm M.00.01.Z1000	
Ratscheneinsatz						
Wir bieten für alle Produktlinien passende Ratscheneinsätze für zahlreiche Drehmomentschlüssel an. Kontaktieren Sie uns gerne.						

